


Note that, for some of the types shown here, order might be unable to be received by the MISUMI Malaysia, and/or Indonesia offices.

Extruded Brackets - For 2 Slots

For 6 Series (Slot Width 8mm) Aluminum Extrusions



Features: Extruded Brackets to connect 2-slot extrusions (HFS6-6060, etc.).

Thick Brackets

NBLTD6
HBLTD6
HBLTD6(-50)
HBLTD6B6 (Black Anodize)
CHBLTD6 (Clear Coating)

For 50 Sq. **HBLTD6-50**

Both sides and screw holes of NBLTD6 is not anodized.

Type	Material	Surface Treatment
NBLTD6	A6063S-T5	Anodize
HBLTD6(-50)		Black Anodize
HBLTD6B6		Clear Coating Anodize + Clear Paint
CHBLTD6	A6N01SS-T5	

Part Number	Mass (g)	Applicable Screw, T Nut				Allowable Load (N)	Unit Price (1-99 pc(s))	Volume Discount Rate (100-200)
		Screw	Quantity	T Nut	Quantity			
NBLTD6	111	CBM6-15	4	HNTT6-6	4	1960		
HBLTD6								
HBLTD6(-50)								
HBLTD6B6								
CHBLTD6								
HBLTD6-50	88							

* For repairing black anodizing, refer to P846.

Features: Numbers of screws are the same as HBLTD6. Extrusions can be connected more securely.

Ultra Thick Brackets

HBLUD6
HBLUD6B6 (Black Anodize)
HBLUD6-50

For 50 Sq. **HBLUD6-50**

Type	Material	Surface Treatment
HBLUD6	A6N01SS-T5	Anodize
HBLUD6B6		Black Anodize
HBLUD6-50		Anodize

Part Number	Mass (g)	Applicable Screw, T Nut				Allowable Load (N)	Unit Price (1-99 pc(s))	Volume Discount Rate (100-200)
		Screw	Quantity	T Nut	Quantity			
HBLUD6	256	CBM6-20	4	HNTT6-6	4	1960		
HBLUD6B6								
HBLUD6-50								

* For repairing black anodizing, refer to P846.

Features: Brackets for 2-slot extrusions with 4 mounting holes on one side can connect extrusions more securely.

Thick Brackets
Triangle Brackets

HBLTDW6
HBLDDW6 (Without Tab)

Example: CBM6-12, HNTT6-6, HBLDDW6

Material: A6N01SS-T5 Surface Treatment: Anodize

Part Number	Mass (g)	Applicable Screw, T Nut				Allowable Load (N)	Unit Price (1-99 pc(s))	Volume Discount Rate (100-200)
		Screw	Quantity	T Nut	Quantity			
HBLTDW6	192	CBM6-15	8	HNTT6-6	8	2940		
HBLDDW6	190	CBM6-12	8	HNTT6-6	8	2940		

Ordering Example: Part Number HBLTD6

Alterations: Part Number HBLTD6 - (C, SET, SST, SEU, SSU, SEP, SSP, SEC)


Alterations	Code	Spec.	Applicable Bracket
Mounting Hole Alteration for Cover	C	Adds taps on a bracket for cover mounting. (M5 on Both Sides) (Mounting Screw HCBM on P.754)	NBLTD6
			HBLTD6
			CHBLTD6
			HBLTD6-50
			HBLUD6
			HBLUD6-50
			HBLTDW6

Alterations	Code	Spec.	Applicable Bracket
Applicable Screws and Nuts Set	SET SST (Stainless Steel)	Applicable screws and nuts for fixing the brackets on extrusions come in a set. (Adds to the bracket price.) (Ex.) When HBLTD6 is specified: Code Screw Nut SET CBM6-15 HNTT6-6 SST SCB6-15 HNTT6-6 SEU CBM6-15 HNTT6-6 SSU SCB6-15 SHNTT6-6 SEP CBM6-15 SHNTT6-6 SSP SCB6-15 SHNTT6-6 SEC HCBST6-20 HNTT6-6	NBLTD6
	SEU		HBLTD6
	SSU		HBLTD6B6
	SEP		CHBLTD6
	SSP		HBLTD6-50
	SEC		HBLUD6
			HBLUD6-50
			HBLTDW6
			HBLUD6
			HBLUD6-50
			HBLTDW6
			HBLDDW6

* Screws for black anodized brackets are HCBMTB (Trivalent Chromate Black) on P.751.
* Included Screw is not RoHS compliant when -SET, -SEU or -SEP other than black anodized brackets is specified.

Extruded Brackets - For 3 or More Slots

For 6 Series (Slot Width 8mm) Aluminum Extrusions



Features: Extruded Brackets to connect Extrusions with 3 slots (HFS6-3090, etc.) with one bracket.

Thick Brackets

NBLTT6
HBLTT6

Both sides and screw holes of NBLTT6 is not anodized.

Type	Material	Surface Treatment
NBLTT6	A6063S-T5	Anodize
HBLTT6	A6N01SS-T5	

Part Number	Mass (g)	Applicable Screw, T Nut				Allowable Load (N)	Unit Price (1-99 pc(s))	Volume Discount Rate (100-200)
		Screw	Quantity	T Nut	Quantity			
NBLTT6	180	CBM6-15	6	HNTT6-6	6	2744		
HBLTT6								

Features: Brackets to connect Extrusions with 3 slots and 4 slots (HFS6-3090, 50100 etc.) with one bracket.

Ultra Thick Brackets

HBLUT6
HBLUF6

Material: A6N01SS-T5 Surface Treatment: Anodize

Part Number	Mass (g)	Applicable Screw, T Nut				Allowable Load (N)	Unit Price (1-99 pc(s))	Volume Discount Rate (100-200)
		Screw	Quantity	T Nut	Quantity			
HBLUT6	409	CBM6-20	8	HNTT6-6	8	2744		
HBLUF6	512						8	2940

Features: Brackets for 3-slot / 4-slot extrusions with 6 / 8 mounting holes on one side can connect extrusions more securely.

Thick Brackets

HBLTTW6
HBLTFW6

Material: A6N01SS-T5 Surface Treatment: Anodize

Part Number	Mass (g)	Applicable Screw, T Nut				Allowable Load (N)	Unit Price (1-99 pc(s))	Volume Discount Rate (100-200)
		Screw	Quantity	T Nut	Quantity			
HBLTTW6	308	CBM6-15	12	HNTT6-6	12	4116		
HBLTFW6	384						16	4410

Ordering Example: Part Number HBLTT6

Alterations: Part Number HBLTT6 - (C, SET, SST, SEU, SSU, SEP, SSP, SEC)

Alterations	Code	Spec.	Applicable Bracket
Mounting Hole Alteration for Cover	C	Adds taps on a bracket for cover mounting. (M5 on Both Sides, Depth 15mm) (Mounting Screw HCBM on P.754)	HBLTT6
			HBLUF6
			HBLTTW6
			HBLTFW6
			HBLTFW6

Alterations	Code	Spec.	Applicable Bracket	
Applicable Screws and Nuts Set	SET SST (Stainless Steel)	Applicable screws and nuts for fixing the brackets on extrusions come in a set. (Adds to the bracket price.) (Ex.) When HBLTT6 is specified: Code Screw Nut SET CBM6-15 HNTT6-6 SST SCB6-15 HNTT6-6 SEU CBM6-15 HNTT6-6 SSU SCB6-15 HNTT6-6 SEP CBM6-15 SHNTT6-6 SSP SCB6-15 SHNTT6-6 SEC HCBST6-20 HNTT6-6	NBLTT6	
	SEU		HBLTT6	
	SSU		HBLTT6	
	SEP		HBLUT6	
	SSP		HBLUF6	
	SEC		HBLTTW6	
			HBLTFW6	

* Included Screw is not RoHS compliant when -SET, -SEU or -SEP are specified.